



Quest Dry RDS 10

Refrigerant Drying System

RDS 10 Specifications

Part No.	4029630
Power	5.1 amps, 110V, Grounded
Water Removal	10 Gallons/day @ 80 °F/60%RH 20 Gallons/day maximum @ saturation
Blower	230 CFM
Operating Range	33 °F to 105 °F
Filters	12" x 12" x 1" Pleated Media MERV-11
Duct Options	Inlet - 12" Flex-Duct Outlet - 10" Lay-Flat
Warranty	Five years; 1st year 100% of Parts and Labor 2nd-5th year 100% of Parts of sealed refrigeration system.

Dimensions

	Machine	Shipping
Width	20"	24"
Height	33.5"	45.25"
Depth	20"	25.5"
Weight	105 lbs	110 lbs

Accessories and Replacement Filters

4029499	Air Filter MERV 11
4029498	Air Filter MERV 7 (Standard)
4029252	Lay Flat Duct 10" Round x 250'
4029521	Flex Duct 12"x25'



Quest Dry RDS 10

ETL Listed



Features:

- Lightweight and Portable - 105 lbs
- High Capacity - Up to 20 gallons at saturation
- Energy Efficiency - Draws only 5.1 amps
- Extended Operating Range - 33 °F to 105 °F
- Process Airflow - 230 CFM
- Durable, Plastic Housing - Resists dents and scratches
- Retractable Handle - A heavy-duty retractable handle for easy storage, transporting and stacking multiple units
- Recessed 12" Wheels - Allows greater maneuverability on the job site and efficient storage. Rolls over obstacles with ease
- Pleated Air Filter
- Inlet Ducting - 12" Flex Duct
- Outlet Ducting - 10" Lay-Flat
- Solid State Controls - Easy to read and operate
- Internal Condensate Pump - Removes water that collects in the reservoir
- Protected Condensate Hose - Recessed hose cannot catch or be damaged on obstructions



Engineered Excellence for Construction Professionals



Specifications subject to change without notice. 05/12



Therma-Stor LLC
4201 Lien Rd
Madison, WI 53704

1-866-933-7486
www.QuestProtect.com
sales@QuestProtect.com