

Quest PowerDry 1300



Refrigerant Drying System

PowerDry 1300 Specifications

Part No.	4032360
Power	5.0 amps, 110V, Grounded
Water Removal	8 Gallons/day @ 80° F/60%RH 16 Gallons/day maximum @ saturation
Process Air	190 CFM
Operating Range	33° F to 100° F
Filter	12" x 12" x 1" Pleated Media MERV-7
Duct Options	Outlet - 10" Lay-Flat
Warranty	Five years; 1st year 100% of Parts and Labor 2nd-5th year 100% of sealed refrigeration system.

Dimensions

	Machine	Shipping
Width	20"	20.5"
Height	30"	35.25"
Depth	17"	18.63"
Weight	79 lbs	93 lbs

Accessories And Replacement Filters

4029252	10" x 250' Lay-flat Duct
4029498	12" x 12" x 1" Pleated Media MERV-7
4029499	12" x 12" x 1" Pleated Media MERV-11



Quest PowerDry 1300

ETL Listed



Features:

- Lightweight and Portable - only 82 lbs. with a small 20"W x 17"D footprint
- High Capacity - Up to 16 gallons/day at saturation
- Energy Efficiency - Draws only 5.0 amps
- Extended operating range up to 100° F; Also operates well in cooler conditions
- Process Airflow - 190 CFM
- Durable, Plastic Housing - Resists dents and scratches
- Rotating Handle - A heavy-duty rotating handle for easy storage, transporting and stacking multiple units
- Recessed 12" Wheels - Allows greater maneuverability on the job site and efficient storage. Rolls over obstacles with ease
- Pleated Media Air Filter
- Front Pocket Storage - For cord and hose storage
- Outlet Ducting - 10" exhaust
- Solid State Controls - Easy to read and operate
- Internal Condensate Pump - Removes water that collects in the reservoir
- Protected Condensate Hose - Recessed hose cannot catch or be damaged on obstructions



Engineered Excellence for
Construction Professionals



Specifications subject to change without notice. 05/12



Therma-Stor LLC
4201 Lien Rd
Madison, WI 53704

1-866-933-7486
www.QuestProtect.com
sales@QuestProtect.com