



Quest PowerDry 4800D Pro

Desiccant Dehumidifier

PowerDry 4800D Pro E (Electric) Specifications

Part No.	4028203 (with Frame) 4029193 (without Frame)
Power	480V three-phase unit, 106 amps
Water	3032 pints/day @ AHAM
Removal	(379 Gallons)
Blower	4800 CFM Process Air
Operating Range	-10°F to 140°F
Duct Options	18" to 20" Flex Duct and Lay Flat
Warranty	2 years; 1st year Parts and Service 2nd year Silica Gel Rotor

Dimensions

Width	48"
Height	56"
Length	112"
Weight	1550 lbs. (desiccant only) 1675 lbs. (desiccant with frame)

Accessories

4029522	Flex Duct 18"x25'
4029256	Lay Flat Duct 18" Round x 250'
4029257	Lay Flat Duct 20" Round x 250'
4029523	Flex Duct 20"x25'

PowerDry 4800D Pro P (Propane) Specifications

Part No.	4028204 (with Frame) 4029194 (without Frame)
Power	240V single-phase unit, 70 amps
Water	3032 pints/day @ AHAM
Removal	(379 Gallons)
Blower	4800 CFM Process Air
Operating Range	-10°F to 140°F
Duct Options	18" to 20" Flex Duct and Lay Flat
Warranty	2 years; 1st year Parts and Service 2nd year Silica Gel Rotor

Dimensions

Width	48"
Height	56"
Length	112"
Weight	1550 lbs. (desiccant only) 1675 lbs. (desiccant with frame)



Quest Dry DDS 375e
(Electric with and
without frame)

Features:

- 3032 pints/day AHAM (379 Gallons)
- 4800 CFM process airflow
- Dries in temperatures to 140°F
- Reaches dew points as low as -40°F
- 48"W x 112"L x 56"H
- 1550 lbs. (desiccant only)
- 1675 lbs. (desiccant with frame)

PowerDry 4800D Pro e

- 480 volt 3-phase
- 106 full load amps

PowerDry 4800D Pro p

- 240V single phase
- 70 amps
- Propane cylinder and trailer mount available



Engineered Excellence for
Construction Professionals



Specifications subject to change without notice. 03/14



Therma-Stor^{llc}
4201 Lien Rd
Madison, WI 53704

1-866-933-7486
www.QuestProtect.com
sales@QuestProtect.com