



Quest Power Air Mover C1000 & C1000 Plus

Air Movers

Power Air Mover C1000 & C1000 Plus Specifications

Power Air Mover C1000
Part Number 4028149

Power Air Mover C1000 Plus
Part Number 4028322

Airflow 2700 FPM

Power 2.8 amps - High Speed
2.4 amps - Low Speed
110V, Grounded

Operating Positions 0°, 45°, 90°

Drive Motor 1/3 Horsepower, 2-Speed

Motor Thermal cut-off

Cord 25 ft Power Cord

Outlet 15A UL Rated GFCI Duplex Receptacle (**C1000 Plus only**)

Warranty Year One - 100% parts and labor (all components)

Year Two - 100% parts only (all components)

Year Three - Parts only on material and workmanship of the housing

Dimensions

	Unit	Shipping
Width	17"	21"
Height	20"	24"
Depth	18"	22"
Weight	26.5 lbs	28 lbs



Power Air Mover C1000

On-board duplex GFCI outlet and circuit breaker (C1000 Plus only)



Power Air Mover C1000 Plus

ETL Listed



Features:

- 2-Speed 1/3 Horsepower Motor with automatic-reset thermal protection.
2.8 Amps on High Speed
2.4 Amps on Low Speed
- Maximum Velocities of 2700 FPM
- Balanced Exhaust Airflow
- Directional Airflow
Horizontal, 45° Angle, 90° Angle
- Durable, rugged, chemical resistant housing, fan wheel, and controls design.
- Operator interface conveniently located for easy access, featuring: power indicator lamp and large three-position switch.
- Pilot Light and Sealed Switch are recessed to prevent damage.
- Ergonomic carry handle and power cord storage.
- Non-marking, anti-skid, rubber feet.
- On-board duplex GFCI outlet and circuit breaker (**C1000 Plus only**)



Engineered Excellence for
Construction Professionals



Specifications subject to change without notice. 11/11



Therma-Stor LLC
4201 Lien Rd
Madison, WI 53704

1-866-933-7486
www.QuestProtect.com
sales@QuestProtect.com